Technical Data Sheet

Issue: January 2025 for professional use only

KAPCI K40 Medium Cut Compound

Product description

KAPCI K40 is a high-performance water-based medium cut compound used for the removal of P2000 or finer (sanding) scratches. It is a silicone and wax free product which delivers a superior gloss finish. KAPCI K40 is used with yellow sponge for polish by machine. It can also be used for polish by hand.

Key benefits of KAPCI K40

✓	Speed	Fast removal of scratches
✓	Finish	Superior gloss finishes
✓	Easy to use	Simple dry use with no water addition and easy removal of the product spatter from adjacent panels
✓	Permanent results	No reappearance of sanding marks

Product Placement in Kapci Polishing System

Fast Cut	Medium Cut	Fine cut	Protection
Kapci K10	Kapci K40	Kapci K60	Kapci K90
Kapci K20			Kapci 80
Kapci K15			Latico 5050
Latico 5000			


Physical, Chemical and General information

Product group	Silicone and wax free
Viscosity	44- 55 Poise
Density	1.05-1.12 kg/L
Shape	Liquid
Color	White
Package	300gm and 0.9L

Technical Information and direction of use

Technical Information	
Cut	7
Gloss	7


IMPORTANT NOTE: These TDS are for information purposes only without any obligation as we do not have control over the quality and conditions of the surface or application

Direction of use		
Maximum abrasion	P2000 or finer	
Polishing tool 	Medium cut foam pad (Yellow)	
Rotational Speed	1200-1800 r.p.m	
Polishing machine 	A rotary or an orbital polishing machine	Apply a small quantity of the product to the pad. Start the machine at medium speed and gradually increase the speed using light pressure.

General notes

- ✓ Apply Kapci K40 out of the direct sunlight.
- ✓ Apply Kapci K40 onto the cool surface.
- ✓ Apply Kapci K40 onto Clean surface.
- ✓ If surface is dry, a little water onto the surface can prevent dust formation.
- ✓ Reduce pressure 2-3 second before the end of rubbing process to get high gloss
- ✓ Remove residue using premium micro fiber cloth.

Storage

	Keep away from frost. Store between 15°C and 35°C. Store in well ventilated area.

Health and Safety

1. For full Health and Safety information refer to the Material Safety Data Sheet (MSDS).
2. Observe the precautionary notices displayed on the container.
3. Goggles and gloves should be worn while using these products.
4. Good ventilation must be provided in the working environment.

IMPORTANT NOTE: These TDS are for information purposes only without any obligation as we do not have control over the quality and conditions of the surface or application